

- · 2 models 9000 to 12 000 Btu/h
- Cooling only
- · Application area: from 12m² to 18m²
- · Backed by Fourways Group nationwide





Alliance Window Wall Range

Ideal for new buildings or as replacements for old units, the new Alliance Window Wall range is available in 2 models of varying dimensions from 9000 to 124000 Btu/h. With indoor sound level as low as 47.6 dB(A) (9000 model), single-phase operation, 3 speeds and EER of 2,81 (all models), these Alliance Window Wall units are perfectly suited for modern buildings and offices. As with all Alliance products, these Window Walls are backed nationwide by Fourways Group in all major metropolitan centres.



	MODEL		FOUW09	F0UW12
Power supply		V,Hz,Ph	220-240V~ 50Hz, 1Ph	220-240V~ 50Hz, 1Ph
Cooling	Capacity	Btu/h	2585	3430
	Input	W	859	1140
	Current	А	3,86	5,04
	EER	W/W	3,01	3,01
Rated input consumption		W	1120	1750
Rated current		А	5.8	9
Starting current		А	20	25
Indoor side air flow(Hi/Mi/Lo)		m3/h	347/315/273	428/377/334
Indoor side noise level (Hi/Mi/Lo)		dB(A)	51.7/49.6/47.6	50.5/48.1/46.4
Outdoor side noise level (Hi/Mi/Lo)		dB(A)	56.3/54.6/53.4	59.5/56.5/52.5
Refrigerant type		kg	R410A/0.43	R410A/0.55
Design pressure		MPa	4.2/1.5	4.2/1.5
Plug type			1.0x3/BS	1.5x3/BS
Control type			Mechanical Control	Mechanical Control
Operation temp	indoor(cooling/heating)	°C	17-32	17-32
	outdoor (cooling/heating)	°C	18-43	18-43
Application area (Cooling Standard)		m ²	12-18	16-23
Dimension(W*D*H)		mm	450x585x346	600x560x380
Packing (W*D*H)		mm	640x505x435	685x620x430
Net/Gross weight		Kg	32.1/34.7	36.8/39.6

Alliance reserves the right to discontinue or change specifications at any time without notice and without incurring obligation. E&OE.



JHB & Central: (011) 704-6320 Bloemfontein: 083 381 0074 Gqeberha (PE): (041) 484-6413 EL: (043) 722-0671 KZN: (031) 579-1895 Pretoria: (012) 643-0445 CPT: (021) 556-8292

