

4 models 9000 to 21 000 Btu/h

Cooling and heating with heat pump technology

- · Indoor air flow up to 901m³ (18 000 model)
- · Application area: from 12m² to 44m²
- · Backed by Fourways Group nationwide





Alliance Window Wall HP Range

Ideal for new buildings or as replacements for old units, the new Alliance Window Wall range is available in 5 models of varying dimensions from 9000 to 24000 Btu/h. With indoor sound level as low as 47.6 dB(A) (9000 model), single-phase operation, 3 speeds and EER of 3.01 (all models), these Alliance Window Wall units are perfectly suited for modern buildings and offices. As with all Alliance products, these Window Walls are backed nationwide by Fourways Group in all major metropolitan centres.



Model			FOUWH09/A	FOUWH12/A	FOUWH18/B	FOUWH21/B
Power supply		V,Hz,Ph	220-1-50	220-1-50	220~240-1-50	220~240-1-50
Cooling	Capacity	Btu/h	9000	1200	1800	2100
		W	2640	3500	5300	6000
	Input	W	939	1245	1600	1830
	Current	Α	4.5	6.1	6.96	7.87
	EER	W/W	2,81	2,81	3,31	3,28
Heating	Capacity	Btu/h	8081.7	10843.8	17050	18755
		W	2370	3180	5000	5500
	Input	W	795	1130	1500	1760
	Current	Α	3.6	5.7	6.50	7.20
	COP	W/W	2.98	2.81	3.33	3.12
Rated input consumption		W	1200	1700	2000	2300
Rated current		Α	6.4	8.6	10.10	11.62
Indoor air flow (Hi/Mi/Lo)		m³/h	400/350/300	450/400/350	850/800/750	850/800/750
Ourdoor air flow (Hi/Mi/Lo)		m³/h	800	850	1800	1800
Indoor noise level (Hi/Mi/lo)		dB(A)	52/50/48	52/50/48	55/53/51	56/54/52
Outdoor noise level (Hi/Mi/lo)		dB(A)	61/59/57	61/59/57	63/61/59	64/62/60
Refrigerant Charge		kg	R410/0.65	R410/0.79	R410/1.30	R410/1.34
Design pressure		Мра	4.3	4.3	4.3	4.3
Throttling Method			Capillary	Capillary	Capillary	Capillary
Application Area		m ²	12-18	16-24	23-34	27-42
Controller			Remote Control	Remote Control	Remote Control	Remote Control
Operational Temp		C°	16-30	16-30	16-30	16-30
Dimension (WxDxH)		mm	450×580×350	560×668x375	660×770×428	660×770×428
Package (W x D x H)		mm	763×620×410	763×620×410	860x736x490	860x736x490
Net/Gross weight		Kg	40/43	47/51	68/73	85/70
Refrigerant			R410A	R410A	R410A	R410A
Refrigerant Charge		Kg	0.65	0.79	1.30	1.34

Alliance reserves the right to discontinue or change specifications at any time without notice and without incurring obligation. E&OE.



JHB & Central: (011) 704-6320 Bloemfontein: 076 466 5158 Gqeberha (PE): (041) 484-6413

EL: (043) 722-0671

KZN: (031) 579-1895 Pretoria: (012) 643-0445 CPT: (021) 556-8292

